

SPECIFICATIONS

120 x 240 V Primary, 12/24 V Secondary

Transformer Type:	Buck Boost
Phase:	Single
Frequency:	60 Hz
kVA:	0.05 to 5 kVA
K Rating:	1
Primary Configuration:	Two Winding
Secondary Configuration:	Two Winding
Reverse Connectable:	Yes
Winding Material:	Copper
Electrostatically Shielded:	No
Temperature Rise:	115°C
Insulation System:	180°C
Enclosure Rating:	NEMA 3R
Enclosure Material:	Steel
Construction Style:	Enclosed - Encapsulated Core & Coil
Mounting Type:	Wall
Connection Type:	Wire Leads
Cooling:	Air/dry
Agency Approvals:	UL Listed, CSA Approved
Warranty:	12 Years



Single Phase
0.5 to 3 kVA



Single Phase
5 to 15 kVA

DIMENSIONS

All dimensions in inches.

Part #	kVA	Weight (lbs)	Length	Width	Height
K1XGF12-0.05	0.05	8	4.25	3.25	8.25
K1XGF12-0.1	0.1	10	4.25	3.25	8.25
K1XGF12-0.15	0.15	14	5	4	9.25
K1XGF12-0.25	0.25	15	5	4	9.25
K1XGF12-0.5	0.5	21	6.5	5.25	11.25
K1XGF12-0.75	0.75	25	6.5	5.25	11.25
K1XGF12-1	1	28	6.5	5.25	11.25
K1XGF12-1.5	1.5	45	7.75	6.25	13.25
K1XGF12-2	2	50	7.75	6.25	13.25
K1XGF12-3	3	60	7.75	6.25	13.25
K1XLF12-5	5	110	10.63	10.19	15